

Metos Multiwasher

MWS700

Multiwasher® is high performance industrial washing machine designed to be ergonomic and user friendly, while delivering the best results. Washes from shopping carts to shipping trays, racks to sheets pans, drums, lugs, dishes and much more.

Designed in a wash cabinet format that optimizes space and achieves the best washing results. Uses 2/3 less water and 70% less soap than other similar industrial washing solutions. A smart energy consumption.

- Internal measurements: 1200x1200x1980 mm
- Spinning Dryer System
- Kit Catering: Diaphragm Rinse Dosing Pump + Impact Variation System

Wash data:

- Tank volume 500 L
- Tank power 31,6 kW
- Tank filling time 30 min (300 kPa)
- Wash pump 15 kW
- Tank wash temperatures 50-80°C
- Washing pressure 1300 kPa (130 bar)
- Wash pump flow 420 l/min

Rinse data:

- Boiler volume 20 L
- Boiler power 21 kW
- Rinse pump 0,46 kW
- Rinse temperature 85°C
- Rinse pressure 300 kPa (3 bar)
- Rinse pump flow 16 l/min
- Water consumption 8 L (30s rinse)

Spinning data:

- Wash rack rotation motor power 0,75 kW
- Exhaust flow 1400 m³/h
- Capsling class IP55
- Automatic detergent dispenser as standard
- Control electronic touch screen
- 20 washing programs

Optional accessory:

- Trolleys
- Lifts



Metos Multiwasher MWS700

Item width mm	2755
Item depth mm	2195
Item height mm	2740
Package volume	20.88
Unit of volume	m3
Package volume	20.88 m3
Package length	300
Package width	240
Package height	290
Package unit of dimension	cm
Package dimensions (LxWxH)	300x240x290 cm
Net weight	1840
Net weight	1840 kg
Gross weight	2590
Package weight	2590 kg
Unit of weight	kg
Connection power kW	47.8
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	55
Remarks (cold water)	tank volume 500 L
Hot water diam.	3/4"
Hot water thread	External thread
Drain diameter	50 mm
Drain thread	Internal thread
Remarks (drain)	water temperature at 85°C
Condense diameter	3/4"
Condense thread	Internal thread

Metos Multiwasher MWS700

Steam diameter	1.1/2"
Steam thread	External thread
Steam conn. inlet	Right;Behind
Ventilation machine m ³ /h	1400
Boiler power kW	21
Boiler volume L	20
Steam consumption kg/h	80
Cleaning	washing program
Washing basket size mm	1200x1200x1980
Programmability	ready programs;programmable
Amount of programs	20
Insulation	insulated
Method of washing	pot wash
Drain pump	No