

Water softener Metos Bestsoft 11

Protects machines optimally from calcification. Simplex soft water plant in compact design. Fully automatic and simple to operate. More output and less salt consumption by proportional salting process. Prefabricated and assembled in the factory for simple installation and start-up. Extended digital control system for maximum performance and efficiency. Rotary valve for higher safety for operations.

- 1 bar pressure loss at nominal flow according to EN14743
- 10 l of ion exchange resins
- 26 m³/°dH nominal capacity
- 4,5 mol nominal capacity
- reserves 12kg of regenerating agent in the cabinet
- 1,5kg salt consumption per regeneration
- 85 l water consumption per regeneration
- Temperature of water (min./max.) 5°C/30°C
- temperature of surrounding (min./max.) 5°C /40°C
- 403 mm connection height for hard water inlet and soft water outlet
- DN50 channel connection (min.)
- operative weight, approx. kg 40

Accessories(sold separately)

- salt
- sanitabs



Water softener Metos Bestsoft 11

Product capacity	1440 litres/hour
Item width mm	270
Item depth mm	480
Item height mm	532
Package volume	0.083
Unit of volume	m3
Package volume	0.083 m3
Package length	30
Package width	50
Package height	55
Package unit of dimension	cm
Package dimensions (LxWxH)	30x50x55 cm
Net weight	10
Net weight	10 kg
Gross weight	10
Package weight	10 kg
Unit of weight	kg
Connection power kW	0.15
Connection voltage V	230
Frequency Hz	50
Protection rating (IP)	51
Cold water diam.	3/4"
Cold water min pressure kPa	100
Cold water max pressure kPa	800
Remarks (cold water)	Weight when in use 40 kg