

# Transp./Serving trolley

## Metos Burlodge RTS CT S 400V3N

Serving trolley for portioned meals on trays in cook-serve operations. The system ensure the taste and microbiology quality of the portions - cold meal items are served cold and warm are served warm! All in accordance with current EU HACCP-regulations. The isolated divider wall divides the chamber and each tray in a hot and a cold part with all meal components on the flat tray. Made for usage of ordinary crockery. Efficient convection heating/refrigeration.

General features:

- Easy daily use: Three different programs (breakfast, lunch, dinner) with 2-phase temperatures and time. Regeneration cycle start manually or timer-controlled. Display with intelligible symbols.
- Light and easy to maneuver: Four vertical, ergonomic handles on each corner. Rubber bumper around the entire trolley base.
- Secure: Digital display shows the chamber temperature in real time and remaining heating cycle. Audible alarm. Surface temperature below +45°C.
- Strong structure: Strong stainless steel AISI304 18/10 frame and inner panels, light weight and shockproof carbon fiber doors reinforced with an aluminum rim. Outer panels antistatic ABS (grey).
- Excellent energy efficiency: high density injected insulation (30 mm). Smart Temp -software considers partial load.
- Hygiene: jet washable, drain with foot pedal. Rated IPX5. Antibacterial material in door latch. Gaskets can be removed without tools for machine dish washing. Wheels with non-marking elastic rubber tyre.



## Transp./Serving trolley Metos Burlodge RTS CT S 400V3N

Product capacity	20 or 24 trays
Item width mm	1025
Item depth mm	780
Item height mm	1475
Package volume	1.508
Unit of volume	m3
Package volume	1.508 m3
Package length	108.6
Package width	87.8
Package height	158.2
Package unit of dimension	cm
Package dimensions (LxWxH)	108.6x87.8x158.2 cm
Net weight	172
Net weight	172 kg
Gross weight	180
Package weight	180 kg
Unit of weight	kg
Connection power kW	7.2
Fuse Size A	11
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Type of electrical connection	Plug
Electrical conn. height mm	1350
Type of the refrigerant	R452a
Quantity of refrigerant g	530
Remarks (refrigeration)	GWP 2141