

# Cold Display Metos Halo 1S1200 LED

Cold LED display with square-shaped design and effective refrigeration made of plexi glass. Cold display is intended for the short-term storage and distribution of pre-refrigerated foodstuffs and beverages

- LED light under front of each shelf
- self-service display with light-weighted doors with handles
- refrigerated basin depth 104 mm ( fits 3 x GN1/1-65 without additional basin supports)
- airflow cools efficiently basin and 2 glass shelves
- tested in climate class 3 (temperature +25 °C and humidity 60 %)
- easily sliding doors in back of display, GN-pans can be easily fitted from the back
- basin easy to remove and clean
- glass shelves made of hardened glass
- automatic evaporation system
- adjustable feet +15 /- 45mm
- stainless steel frame structure

Accessories/features, to be ordered separately:

- handle-free doors
- laminated panelling
- flat or tube-shaped tray slides
- kick plates
- air flow grid
- adaptation for central cooling and drainage
- covering plate in front to achieve even colder display temperatures



## Cold Display Metos Halo 1S1200 LED

Product capacity	3 x GN1/1 -65
Item width mm	1200
Item depth mm	650
Item height mm	1500
Package volume	2.016
Unit of volume	m3
Package volume	2.016 m3
Package length	140
Package width	80
Package height	180
Package unit of dimension	cm
Package dimensions (LxWxH)	140x80x180 cm
Net weight	202.34
Net weight	202.34 kg
Gross weight	230
Package weight	230 kg
Unit of weight	kg
Connection power kW	0.9
Fuse Size A	10
Connection voltage V	220-240
Number of phases	1NPE
Frequency Hz	50
Startup current A	6.5
Protection rating (IP)	43
Type of electrical connection	Plug
Type of the refrigerant	R290
Quantity of refrigerant g	140