

Upper shelf Proff US-1600- 1H

Construction and upper shelf made of stainless steel. Width of
s/s upper shelf 280 mm

- one-sided sneeze guard of tempered glass
- halotherm heating lamps



Upper shelf Proff US-1600-1H

| | |
|-------------------------------|--------------|
| Item width mm | 1600 |
| Item depth mm | 507 |
| Item height mm | 405 |
| Package volume | 0.356 |
| Unit of volume | m3 |
| Package volume | 0.356 m3 |
| Package length | 160 |
| Package width | 53 |
| Package height | 42 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 160x53x42 cm |
| Net weight | 15 |
| Net weight | 15 kg |
| Gross weight | 15 |
| Package weight | 15 kg |
| Unit of weight | kg |
| Connection power kW | 0.6 |
| Fuse Size A | 16 |
| Connection voltage V | 230 |
| Number of phases | 1NPE |
| Frequency Hz | 50/60 |
| Startup current A | 3.5 |
| Protection rating (IP) | 43 |
| Type of electrical connection | Semifixed |

Upper shelf Proff US-1600-1H

| | |
|----------------|-------|
| Item width mm | 1600 |
| Item depth mm | 650 |
| Item height mm | 900 |
| Package volume | 1.271 |
| Unit of volume | m3 |

Upper shelf Proff US-1600-1H

| | |
|-------------------------------|-----------------------------|
| Package volume | 1.271 m3 |
| Package length | 165 |
| Package width | 70 |
| Package height | 110 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 165x70x110 cm |
| Net weight | 85 |
| Net weight | 85 kg |
| Gross weight | 105 |
| Package weight | 105 kg |
| Unit of weight | kg |
| Connection power kW | 2.8 |
| Fuse Size A | 16 |
| Connection voltage V | 230 |
| Number of phases | 1NPE |
| Frequency Hz | 50 |
| Startup current A | 13 |
| Protection rating (IP) | 43 |
| Type of electrical connection | Plug |
| Operation type | electromechanical |
| Cleaning | hand wash |
| GN size | GN4/1 210 mm + 12 GN1/1-100 |
| Number of chambers | 4 |
| Power range kW | 2.8 |
| Lighting | without lighting |
| Fill in trolleys | No |
| Humidification | No |
| Timer | No |

Upper shelf Proff US-1600-1H

| | |
|---------------|------|
| Item width mm | 1600 |
|---------------|------|

Upper shelf Proff US-1600-1H

| | |
|-------------------------------|----------------------|
| Item depth mm | 650 |
| Item height mm | 900 |
| Package volume | 1.271 |
| Unit of volume | m3 |
| Package volume | 1.271 m3 |
| Package length | 165 |
| Package width | 70 |
| Package height | 110 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 165x70x110 cm |
| Net weight | 95 |
| Net weight | 95 kg |
| Gross weight | 115 |
| Package weight | 115 kg |
| Unit of weight | kg |
| Connection power kW | 2.8 |
| Fuse Size A | 16 |
| Connection voltage V | 230 |
| Number of phases | 1NPE |
| Frequency Hz | 50 |
| Startup current A | 13 |
| Protection rating (IP) | 43 |
| Type of electrical connection | Plug |
| Operation type | electromechanical |
| Cleaning | hand wash |
| GN size | 4x1/1 + 12 GN1/1-100 |
| Number of chambers | 4 |
| Power range kW | 2.8 |
| Lighting | without lighting |

Upper shelf Proff US-1600-1H

| | |
|------------------|----|
| Fill in trolleys | No |
| Humidification | No |
| Timer | No |

Upper shelf Proff US-1600-1H

| | |
|-------------------------------|-------------------|
| Item width mm | 1600 |
| Item depth mm | 650 |
| Item height mm | 900 |
| Package volume | 0.965 |
| Unit of volume | m3 |
| Package volume | 0.965 m3 |
| Package length | 165 |
| Package width | 65 |
| Package height | 90 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 165x65x90 cm |
| Net weight | 100 |
| Net weight | 100 kg |
| Gross weight | 100 |
| Package weight | 100 kg |
| Unit of weight | kg |
| Connection power kW | 2.2 |
| Fuse Size A | 16 |
| Connection voltage V | 230 |
| Number of phases | 1NPE |
| Frequency Hz | 50 |
| Startup current A | 9.6 |
| Protection rating (IP) | 43 |
| Type of electrical connection | Plug |
| Operation type | electromechanical |
| Cleaning | hand wash |

Upper shelf Proff US-1600-1H

| | |
|----------------|-----------|
| GN size | GN4/1-210 |
| Power range kW | 2.2 |

| | |
|------------------|------------------|
| Lighting | without lighting |
| Fill in trolleys | No |
| Humidification | No |
| Timer | No |

Upper shelf Proff US-1600-1H

| | |
|----------------------------|--------------|
| Item width mm | 1600 |
| Item depth mm | 650 |
| Item height mm | 900 |
| Package volume | 0.965 |
| Unit of volume | m3 |
| Package volume | 0.965 m3 |
| Package length | 165 |
| Package width | 65 |
| Package height | 90 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 165x65x90 cm |
| Net weight | 60 |
| Net weight | 60 kg |
| Gross weight | 67 |
| Package weight | 67 kg |
| Unit of weight | kg |
| Connection power kW | 2.2 |
| Fuse Size A | 16 |
| Connection voltage V | 230 |
| Number of phases | 1NPE |
| Frequency Hz | 50 |
| Startup current A | 10 |
| Protection rating (IP) | 43 |

Upper shelf Proff US-1600-1H

| | |
|-------------------------------|-------------------|
| Type of electrical connection | Plug |
| Operation type | electromechanical |
| Cleaning | hand wash |
| GN size | GN1/1-210 |

| | |
|------------------|------------------|
| Power range kW | 2.2 |
| Lighting | without lighting |
| Fill in trolleys | No |
| Humidification | No |
| Timer | No |