

Blast chiller tunnel Metos MBC602SB-RT-CO2

For 3 GN 2/1 oven trolleys or 6 GN 1/1 trolleys. Floorless

- two doors tunnel type
- inner depth 3350 mm
- door opening width 880 mm
- net height door 1820 mm
- chilling capacity 420 kg
- extraction capacity(-10 / + 45 ° C) 52750 W
- panel construction
- stainless steel exterior (Scotch-Brite satin)
- inner in stainless steel with rounded corners
- inside bottom and floor die-formed leakproof
- insulation in high density (42 kg/m³ approx.) expanded polyurethane, 80 mm thick, HCFC-free
- copper-aluminum evaporator with cataphoresis anti-corrosion treatment
- high-ventilation evaporator to ensure the highest efficiency of the cooling system
- anti-condensation resistance, placed on the door under the gasket
- hinged door with gasket and closing ramp system
- vertical ergonomic door handle with magnetic closure
- thick stainless steel internal bumper to avoid damage caused by the trolley
- external stainless steel protection to protect the control-board
- heated core probe, with 4 measuring points
- standard active chamber sterilization system with active ions (HI-GIENE) activated by the control
- pre-cooling function
- PLUS functions
- adjustment of the speed of the evaporator fans
- automatic storing at end of blast chilling
- indirect blowing electronic fans, efficient but gentle on food
- 7" high-definition IPS capacitive TOUCH display, easy to use
- processes identifiable through photos
- USB connection for uploading and downloading



data and recipes

- circuit breaker for compressor protection
- electrical connections positioned frontally in the panel equipped with safety locks
- class T (ambient temperature + 43 ° C)
- remote condensing unit and possibility to have stainless steel protective cover
- refrigerant CO2 data and recipes
- circuit breaker for compressor protection
- electrical connections positioned frontally in the panel equipped with safety locks
- class T (ambient temperature + 43 ° C)
- remote condensing unit and possibility to have stainless steel protective cover
- refrigerant CO2

Blast chiller tunnel Metos MBC602SB-RT-CO2

| | |
|-------------------------------|-------------------|
| Product capacity | 3 trolleys GN 2/1 |
| Item width mm | 1500 |
| Item depth mm | 3860 |
| Item height mm | 2140 |
| Package volume | 22.133 |
| Unit of volume | m3 |
| Package volume | 22.133 m3 |
| Package length | 240 |
| Package width | 530 |
| Package height | 174 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 240x530x174 cm |
| Net weight | 1266 |
| Net weight | 1266 kg |
| Gross weight | 1573 |
| Package weight | 1573 kg |
| Unit of weight | kg |
| Connection power kW | 14.34 |
| Fuse Size A | 25 |
| Connection voltage V | 400 |
| Number of phases | 3NPE |
| Frequency Hz | 50 |
| Protection rating (IP) | 54 |
| Type of electrical connection | Semifixed |
| Cooling capacity W | 52750 |
| Type of the refrigerant | CO2 |
| Cooling unit | Remote cooled |

metos

BC/BF602SB-RT

- Ⓜ INGRESSO REFRIGERANTE
REFRIGERANT INLET
- Ⓜ USCITA REFRIGERANTE
REFRIGERANT OUTLET
- Ⓜ CONNESSIONE ELETTRICA
ELECTRICAL CONNECTION
- Ⓜ CONNESSIONE SCARICO
DRAIN CONNECTION
- DIMENSIONI mm
DIMENSIONS [in]

