

Blast chiller room Metos

MBC602SB-RI

For 3 GN 2/1 oven trolleys or 6 GN 1/1 trolleys. Floorless

- roll-in model
- inner depth 3350 mm
- door opening width 880 mm
- net height door 1820 mm
- chilling capacity 420 kg
- extraction capacity(-10 / + 45 ° C) 52750 W
- panel construction
- stainless steel exterior (Scotch-Brite satin)
- inner in stainless steel with rounded corners
- inside bottom and floor die-formed leakproof
- insulation in high density (42 kg/m³ approx.) expanded polyurethane, 80 mm thick, HCFC-free
- copper-aluminum evaporator with cataphoresis anti-corrosion treatment
- high-ventilation evaporator to ensure the highest efficiency of the cooling system
- anti-condensation resistance, placed on the door under the gasket
- hinged door with gasket and closing ramp system
- vertical ergonomic door handle with magnetic closure
- thick stainless steel internal bumper to avoid damage caused by the trolley
- external stainless steel protection to protect the control-board
- heated core probe, with 4 measuring points
- standard active chamber sterilization system with active ions (HI-GIENE) activated by the control
- pre-cooling function
- PLUS functions
- adjustment of the speed of the evaporator fans
- automatic storing at end of blast chilling
- indirect blowing electronic fans, efficient but gentle on food
- 7" high-definition IPS capacitive TOUCH display, easy to use
- processes identifiable through photos
- USB connection for uploading and downloading data



and recipes

- circuit breaker for compressor protection
- electrical connections positioned frontally in the panel equipped with safety locks
- class T (ambient temperature + 43 ° C)
- remote condensing unit and possibility to have stainless steel protective cover and recipes
- circuit breaker for compressor protection
- electrical connections positioned frontally in the panel equipped with safety locks
- class T (ambient temperature + 43 ° C)
- remote condensing unit and possibility to have stainless steel protective cover

Blast chiller room Metos MBC602SB-RI

Product capacity	540kg/+70...+3°C
Item width mm	1500
Item depth mm	3730
Item height mm	2040
Package volume	22.133
Unit of volume	m3
Package volume	22.133 m3
Package length	240
Package width	530
Package height	174
Package unit of dimension	cm
Package dimensions (LxWxH)	240x530x174 cm
Net weight	1220
Net weight	1220 kg
Gross weight	1573
Package weight	1573 kg
Unit of weight	kg
Connection power kW	18.364
Fuse Size A	32
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	54
Type of electrical connection	Semifixed
Cooling capacity W	27960
Condensing temperature °C	+45
Evaporation temperature °C	-25
Type of the refrigerant	R452A/R448A/R449A
Remarks (refrigeration)	Remote cooling

Blast chiller room Metos MBC602SB-RI

Cooling unit

Remote cooled