

## Cold room MSRC 2727 230V 1N~

Cold area +2...+6°C. Supplied in elements

- 80mm polyurethane insulation
- automatic temperature control and electronic thermostat with number display
- automatic defrost and evaporation of condensation water
- supplied with 4 shelf tiers, made of white-painted steel plate, adjustable every 17mm.
- interior and exterior finish of steel plate with white polyester coating
- lockable door and interior light
- Optional extras: room without floor elements, extra shelves available in s/s



## Cold room MSRC 2727 230V 1N~

|                               |                |
|-------------------------------|----------------|
| Product capacity              | 11870 l        |
| Item width mm                 | 2700           |
| Item depth mm                 | 2700           |
| Item height mm                | 2100           |
| Package volume                | 5.831          |
| Unit of volume                | m3             |
| Package volume                | 5.831 m3       |
| Package length                | 132            |
| Package width                 | 155            |
| Package height                | 285            |
| Package unit of dimension     | cm             |
| Package dimensions (LxWxH)    | 132x155x285 cm |
| Net weight                    | 465            |
| Net weight                    | 465 kg         |
| Gross weight                  | 475            |
| Package weight                | 475 kg         |
| Unit of weight                | kg             |
| Connection power kW           | 0.92           |
| Fuse Size A                   | 10             |
| Connection voltage V          | 230            |
| Number of phases              | 1N             |
| Frequency Hz                  | 50             |
| Type of electrical connection | Plug           |
| Electrical conn. height mm    | 2100           |
| Type of the refrigerant       | R404A          |
| Quantity of refrigerant g     | 750            |