


## Freezer room MSRF 2415

### 230V 1N~

- Cold area -18...-22°C. Supplied in elements
- 80mm polyurethane insulation
  - automatic temperature control and electronic thermostat with number display
  - automatic defrost and evaporation of condensation water
  - supplied with 4 shelf tiers, made of plastic accepted in food industry , adjustable every 50 mm.
  - interior and exterior finish of steel plate with white polyester coating
  - lockable door and interior light
  - Optional extras: room without floor elements, extra shelves available in s/s, floor heat resistance



## Freezer room MSRF 2415 230V 1N~

Product capacity	5550 l
Item width mm	2400
Item depth mm	1500
Item height mm	2100
Package volume	3.55
Unit of volume	m3
Package volume	3.55 m3
Package length	100
Package width	155
Package height	229
Package unit of dimension	cm
Package dimensions (LxWxH)	100x155x229 cm
Net weight	580
Net weight	580 kg
Gross weight	590
Package weight	590 kg
Unit of weight	kg
Connection power kW	1.33
Fuse Size A	16
Connection voltage V	230
Number of phases	1N
Frequency Hz	50
Type of electrical connection	Plug
Electrical conn. height mm	2100
Type of the refrigerant	R290
Quantity of refrigerant g	149