

High Speed oven Metos Merrychef Connex12 High Power Black

The black Metos Merrychef High Power ConneX®12 is the most versatile, high speed oven on the market. An all-in-one unit ideally suited to rapidly cook, toast, grill and reheat fresh or frozen food, eliminating the need for other appliances. Cooking up to 20x faster than other cooking methods it can provide hot food on demand.

- High speed Technology® combines three heat technologies: / Microwave max 2000W; Microwave setting options: Off and 5-100% in 1% increments. Microwave distribution system uses a rotating active antenna to ensure even heating throughout the food. / Convection max 2200W; Temperature setting options: Off and 100°C to 275°C in 1°C increments. / The Heat distribution system is via Tuned Impingement, ensuring the most even browning. / Combination mode 2000W+2200W
- Large cavity 30.5cm x 30.5cm to oven width 35.5cm ratio, and fits on a 600mm worktop, perfect when space is at a premium
- Easy to install due to ventless cooking capabilities through a built- in catalytic converter, eliminates the need for an extraction fan
- Cool to touch exterior makes it safe to locate anywhere with no need to allow space around the unit
- Easy to operate with a 7" HD widescreen display and new generation easyTouch®2.0, icon driven controller, ensuring consistent, high quality dishes
- Stainless steel cavity and casework, with a sealed rounded edged cavity makes it easy to clean
- Patented easy access front mounted monitored air filter
- Wi-fi/ethernet connected with access to KitchenConnect cloud for easy menu updates (or, via a



USB memory stick)

- Black finish

Included accessories / Flat cook plate / Guarded hand paddle with supporting side walls / Cooking tray, full size / Cool down pan / Cook plate liner USB memory stick)

- Black finish

Included accessories / Flat cook plate / Guarded hand paddle with supporting side walls / Cooking tray, full size / Cool down pan / Cook plate liner

High Speed oven Metos Merrychef Connex12 High Power Black

Product capacity	cavity 35,5x30,5x30,5cm
Item width mm	356
Item depth mm	648
Item height mm	629
Package volume	0.367
Unit of volume	m3
Package volume	0.367 m3
Package length	52
Package width	82
Package height	86
Package unit of dimension	cm
Package dimensions (LxWxH)	52x82x86 cm
Net weight	50
Net weight	50 kg
Gross weight	60
Package weight	60 kg
Unit of weight	kg
Connection power kW	6.9
Fuse Size A	32
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	X3
Electrical cable length mm	1800
Type of electrical connection	Semifixed
Sound level dB	65