

Food transport trolley

Termia 1000CN 125

OUTLET

Metos Termia 1000 CN, easily maneuvered cold trolley for transport and storage of food. Washable in trolley washer

Technical specification: Exterior walls: Stainless steel Inner container: Welded container in stainless steel Guides: C-type guides of stainless steel, 78mm spacing. Suitable for GN 1/1, GN 1/2, GN 2/3, GN 1/3 Insulation: Polyurethane foam Door: The door is made of smooth and seamless stainless steel. Firmly lockable door with silicon sealing, door opens to the side, secure by magnet in open position Wheels: Stainless steel 125mm rubber castors with ball bearings, two fixed and two swivel castors with brakes Top Frame: Stainless steel Trolley frame: Reject list of stainless steel coated with PVC

Options:

- 160 mm castors, two fixed and two swivel castors with brakes
- towing set
- central brake



Food transport trolley Termia 1000CN 125 OUTLET

| | |
|-------------------------------|----------------------|
| Product capacity | 8 x GN1/1-65 |
| Item width mm | 540 |
| Item depth mm | 907 |
| Item height mm | 1000 |
| Package volume | 0.503 |
| Unit of volume | m ³ |
| Package volume | 0.503 m ³ |
| Package length | 91 |
| Package width | 55 |
| Package height | 100.5 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 91x55x100.5 cm |
| Net weight | 69 |
| Net weight | 69 kg |
| Gross weight | 74 |
| Package weight | 74 kg |
| Unit of weight | kg |
| Connection power kW | 0.35 |
| Fuse Size A | 10 |
| Connection voltage V | 230 |
| Number of phases | 1NPE |
| Frequency Hz | 50/60 |
| Startup current A | 1.5 |
| Protection rating (IP) | X6 |
| Type of electrical connection | Plug |