

Griddle smooth Metos Diamante D72/10TFTE table top model

The Metos Diamante 70 D72/10TFTE electric grill table top model has a smooth steel surface. The grill has the temperature of which can be regulated between 110 °C...280 °C. The control panel has an indicator light, which illuminates when the grill zone is switched on. The grill surface is welded to the exterior of the unit and is recessed by 40 mm, which provides a greater cooking surface and prevents dirt from collecting between the exterior and the surface of the grill. In addition, the grill surface can be inclined 10 mm to the front, which allows grease to flow into the large grease trap.



Every detail of the strong, stylish and hygienic restaurant range series Metos Diamante 70 has been planned as an efficient and functioning solution, from pre-treatment to the preparation of the food itself, without forgetting the need to easily clean the range. Diamante 70 series ranges are available as a table top model as well as with its own cupboard, as single or multiple combined units, and are suitable for use in small to mid-sized to large kitchens. Laser cut hobs allow for the seamless joining together of units into cleanly connected islands or lines in places of heavy use, such as large kitchens.

- table top model
- smooth steel surface;
- large splash proof control knobs;
- overheating protection.

EXTRA ACCESSORIES (can be ordered separately):

- splash guard;
- open stand
- stand with guide rails
- cupboard doors;
- cupboard doors for utensil frames;
- utensil frames; knife rack, utensil rack, spice

rack frame, spice jar rack;

- drawer for the cupboard;

- with a heated bottom;

- socket;

- side panels. rack frame, spice jar rack;

- drawer for the cupboard;

- with a heated bottom;

- socket;

- side panels.

Griddle smooth Metos Diamante D72/10TFTE table top model

Item width mm	400
Item depth mm	730
Item height mm	250
Package volume	0.108
Unit of volume	m3
Package volume	0.108 m3
Package length	45
Package width	80
Package height	30
Package unit of dimension	cm
Package dimensions (LxWxH)	45x80x30 cm
Net weight	47
Net weight	47 kg
Gross weight	57
Package weight	57 kg
Unit of weight	kg
Connection power kW	5.4
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50/60
Protection rating (IP)	X4