

Bain Marie trolley Metos Luna BM 800x650x900

The Bain Marie trolley Metos Luna BM is self-service unit equipped with wheels. In the standard model, two of the four wheels can be locked. The food distribution units can be used either alone or they can be used to build a self-service line suitable for the customer's individual needs. At its best, the flexibility of the model comes out in customer-specific solutions, for which the modularity gives numerous possibilities.

The Bain Marie trolley has S/S tray slides with a width of 250mm. The upper part is stainless steel with LED light, which illuminates the food from above. The depth of the bain marie is 160 mm and maximum temperature is 90°C. The rounded inner corners of the GN-1/1 dimensioned basins make cleaning easier. The high-pressure laminate liners are standard in gray F7912 color. A connecting piece with which the units can be connected to each other is included in the delivery.

- Seamless cover and rounded inner corners of the basin, depth 160mm
- maximum temperature of the bain marie 90°C
- Leveled tray levels 250mm, both sides of the unit
- Durable stainless steel frame, lining plates high-pressure laminate, Standard color: gray F7912
- The edge band is neutral gray color
- Light-running wheels, two of which are lockable, standard diameter 125mm
- The furniture has doors for easy access to the switches
- Drained basin; basin-specific drain valve
- Connecting piece for connecting units together
- Stainless steel top shelf, with a LED light underneath
- Tempered glass sneeze guard on both



sides sides

Bain Marie trolley Metos Luna BM 800x650x900

Product capacity	2xGN1/1
Item width mm	800
Item depth mm	650/1150
Item height mm	900/1280
Package volume	0.774
Unit of volume	m3
Package volume	0.774 m3
Package length	85
Package width	70
Package height	130
Package unit of dimension	cm
Package dimensions (LxWxH)	85x70x130 cm
Net weight	95
Net weight	95 kg
Gross weight	105
Package weight	105 kg
Unit of weight	kg
Connection power kW	1.12
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50/60
Startup current A	4.86
Protection rating (IP)	43
Function	warm
GN size	2xGN1/1 160
Power range kW	1.1
Lighting	LED
Upper part	with upper part

Bain Marie trolley Metos Luna BM 800x650x900