

# Rack conveyor machine

## METOS WD-241E TOUCH L-R

Metos WD 241E TOUCH- Rack conveyor machine is reliable and cost-effective rack conveyor machine with unique basket feed system allows operators to adjust their contact time and the capacity depending on how heavily soiled the dishware is. TOUCH DISPLAY is self-explanatory and angled, made in tempered glass. Works even if you are wearing gloves or have wet hands.

Feeding direction left-right, length 2555mm incl. Loading hood 170mm, Prewash 900mm, Chemical wash 900mm, Triple final rinse 585mm.

- Infeed size 538'440mm
- User-friendly - Ergonomically designed to provide a good working environment
- The WD-Touch display guides you through the washing process with an intuitive touch screen and ensures the washing temperature. Easy navigation with built-in user manuals. Quick error reporting simplifies servicing and minimizes unnecessary downtime.
- Low operating costs and a reduced environmental impact
- Triple rinse for reduced final rinse water consumption
- Excellent wash results - Long washing zones with powerful pumps
- Long service life and easy servicing- Made entirely of stainless steel
- Improved hygiene with vertical self-emptying wash- and rinse pumps
- Electrical connection of PRE-RINSE by the dishwasher
- PRE-RINSE using excess water from the dishwasher
- Electricity and water connections from top
- Drain integrated in the machine for easy cleaning and draining
- ECO-FLOW - condensing unit with heat recovery by the exhausted steam
- Wash arms in stainless steel, with quick fit/



removal function. Easily cleaned and without end covers

- Removable doors for the periodical cleaning
- Easy servicing - the machine is serviced from the front
- Single lever for emptying the tanks, automatic closing of tanks when refilling is starting
- Monitoring system of the machine's various functions - Panel which displays the information
- Web Tool with HACCP documentation
- Contactor for entry and exit conveyor. Note! It's always necessary to specify the motor power of the conveyor.

If not specified, protective motor switch of 0,63-1A will be delivered. OPTIONS

- Pre-rinse zone L=400 mm
- Drying zone WD-T60 L=600 mm, insulated. Power 3,3 kW.
- Stand with grid shelf
- Stand with plane shelf
- Drying zone WD-T80, to turn track L=820 mm, insulated, for connection to the or machine driven WD turn track. Power 3,3 kW.
- Double drying zone WD-T90 L=900 mm, insulated. With stand. Power 6,6 kW.
- Grid shelf
- Plane shelf
- Divided between machine and drying zone
- 230V/3/50Hz and marine version and other voltage selection on request
- Steam heated design, steam pressure 50-149 kPa
- Steam heated design, steam pressure 150 - 250 kPa
- Break tank included with booster pump
- Booster heater 12 kW for re-circulating final rinse
- RO-water connection
- Stainless pipes and couplings in final rinse
- Cold water connection
- Water connection from floor
- Timer for pre-rinse
- Timer for through-rinse
- Timer for chain-rinse
- Timer start, machine ready for wash
- Contactor for control of pre-rinse without timer
- Contactor for pre-rinse with booster pump
- Connection power restriction for example Sicotronic
- External power indication
- Auto self-cleaning of wash zone
- Auto self-cleaning of condense battery
- Auto self-cleaning of wash zone + condense battery
- Web Tool with HACCP documentation for cost- and consumption report
- Possibility to interlock the booster heater

#### EXTRA EQUIPMENT

- Ask more from Metos Sales
- Conduit for connection cable, L=1200 mm

#### TECHNICAL DATA

- Pump, pre-wash (kW) 1.5
- Pump, chemical wash 1 (kW) 1.5
- Pump, chemical wash 2 (kW) -
- Pump, chemical wash 3 (kW) -
- Pump, recirculating final rinse (kW)

0.11

- Fan, heat recovery (kW) 0.12
- Motor, feeder (kW) 0.12
- Booster heater 1 (kW) 12
- Booster heater 2 (kW) 12
- Heater, chemical wash 1 (kW) 12
- Heater, chemical wash 2 (kW) -
- Heater, chemical wash 3 (kW) -
- Heat recovery unit, cooling area (m<sup>2</sup>) 25
- Fan heat recovery, capacity (m<sup>3</sup>/h) 100
- Tank volume, pre-wash tank (liters) 77
- Tank volume, wash tank 1 (liters) 100
- Tank volume, wash tank 2 (liters) -
- Tank volume, wash tank 3 (liters) -
- Tank volume, final rinse tank (liters) 6
- Weight, dishwasher in operation (kg) 655
- Degree of protection (IP) 55
- Total connected power (kW) 40.1
- Main fuse 400V 3N~(A)\* 63
- Max. connection area 400V 3N~(L1-L3, N, PE) Cu (mm<sup>2</sup>) 35,,
- Hot water connection 50-65°C (internal thread) R ½"
- Cold water connection 5-12°C (internal thread) R ½"
- Drain connection, PP pipe (ø mm) 50
- Water capacity, pressure (kPa) 250-600
- Water capacity, flow (liters/min) 11
- Floor drain, capacity (liters/sec) 3
- Heat load to the room (total, sensible, latent) (kW) 9 / 5.3 / 3.7

#### CAPACITY AND OPERATING DATA

- Capacity normal wash (baskets/h) 110-210\*
- Capacity according to DIN 10510 (baskets/h) 140
- Max capacity interlocked booster heater (baskets/h) 200
- Cold water consumption, final rinse normal (liters/basket) 1.5
- Sound level (dB) 68

... more details on our web pages

## Rack conveyor machine METOS WD-241E TOUCH L-R

Product capacity	140 basket/hour (DIN 10510)
Item width mm	2555
Item depth mm	697
Item height mm	1675/1950
Package volume	4.8
Unit of volume	m3
Package volume	4.8 m3
Package length	300
Package width	80
Package height	200
Package unit of dimension	cm
Package dimensions (LxWxH)	300x80x200 cm
Net weight	485
Net weight	485 kg
Gross weight	550
Package weight	550 kg
Unit of weight	kg
Connection power kW	40.1
Fuse Size A	63
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	55
Electrical conn. height mm	1675
Cold water diam.	1/2"
Cold water flow l/min	11
Cold water min pressure kPa	250
Cold water max pressure kPa	600
Cold water conn. height mm	1820

## Rack conveyor machine METOS WD-241E TOUCH L-R

Hot water diam.	1/2"
Hot water thread	Internal thread
Hot water flow l/min	11
Hot water min pressure kPa	100
Hot water max pressure kPa	600
Hot water conn. height mm	1785
Drain diameter	50
Drain flow l/s	3
Drain conn. inlet	Right;Behind;Bottom
Drain conn. height mm	187
Floor drain needed	Yes
Sound level dB	68
HACCP-connectivity	YES
Heat load sensitive W	5300
Heat load latent W	3700
Boiler power kW	24
Power type	electric
Operation type	electronical
Cleaning	hand wash
Washing basket size mm	500x500
Programmability	ready programs
Amount of programs	2
Insulation	insulated
Method of washing	normal wash
Drain pump	No
Model	WD-E TOUCH