

Dishwasher Metos WD-4S

Eco-Flow +booster heater

Metos WD-4S Eco-Flow is high-quality scandinavian manufacture; reliable and versatile undercounter dishwasher for demanding use in professional kitchens. Metos WD-4S machines have an efficient acoustic and thermal insulation. The construction is of stainless steel and tempered glass, easy to keep clean.

Metos WD-4S Eco-Flow has an inbuilt drain pump. The machine has three washing programmes; P1 for cups and glasses (wash time 1.2 min), P2 for plates (2.4 min) and P3 for cutlery and pots (4.2 min). Washing and rinsing times are programmable according to particular needs. Low temperature warning. If the rinse temperature falls below the set level, the machine goes on washing until the correct rinse temperature is reached. The stainless steel wash arms cover every millimetre of the dishware. The wash arms are emptied of washing water when the final rinse starts, ensuring that they do not drip and cause spots on the clean items.

The self-explanatory display in tempered glass gives you a clear overview of the washing time from a distance. Colours indicate the status of the wash and a sound indicates when the wash cycle is complete. The smart display also works if you are wearing gloves or have wet hands. The machine's memory allows the reading of the number of the baskets washed, daily and for the whole usage time. Metos WD-4S connection is three-phased, but it can be converted to one-phased on installation.

- three washing programmes 1.2 / 2.4 / 4.2 min
- push of button easily changes water
- space enough to wash trays up to 530 x 330 mm



- also GN1/1 canteens
- basket size 500x500 mm
- the final rinse temperature is guaranteed to 85° C
- automatic self-cleaning function
- new door position keeping it slightly open
- diagnostic function
- inbuilt breaktank and booster pump
- water consumption appr. 2.4 l/basket
- tank volume 20 l
- additional heater 6,9 kW

DELIVERY INCLUDES:

- condensing unit with heat recovery
- cold water connection
- booster heater 6,9 kW
- detergent dispenser
- rinse aid dispenser
- drain pump
- tank strainers 2 pcs
- baskets for plates
- baskets for cups
- baskets for cutlery

ACCESSORIES (ordered separately):

- stand with basket rails
- stand cabinet
- water absorbent mat
- also GN1/1 canteens
- basket size 500x500 mm
- the final rinse temperature is guaranteed to 85° C
- automatic self-cleaning function
- new door position keeping it slightly open
- diagnostic function
- inbuilt breaktank and booster pump
- water consumption appr. 2.4 l/basket
- tank volume 20 l
- additional heater 6,9 kW

DELIVERY INCLUDES:

- condensing unit with heat recovery
- cold water connection
- booster heater 6,9 kW
- detergent dispenser
- rinse aid dispenser
- drain pump
- tank strainers 2 pcs
- baskets for plates
- baskets for cups
- baskets for cutlery

ACCESSORIES (ordered separately):

- stand with basket rails

- stand cabinet

- water absorbent mat

Dishwasher Metos WD-4S Eco-Flow +booster heater

Product capacity	35 baskets / hour
Item width mm	600
Item depth mm	600
Item height mm	820+55
Package volume	0.38
Unit of volume	m3
Package volume	0.38 m3
Package length	65
Package width	65
Package height	90
Package unit of dimension	cm
Package dimensions (LxWxH)	65x65x90 cm
Net weight	60
Net weight	60 kg
Gross weight	70
Package weight	70 kg
Unit of weight	kg
Connection power kW	7.65
Fuse Size A	16
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	44
Electrical conn. diam. mm	2,5
Electrical cable length mm	2000
Type of electrical connection	Semifixed
Remarks (electrical)	Booster Heater 6,9 kW
Remarks (cold water)	cold water connection
Hot water diam.	R3/4"

Dishwasher Metos WD-4S Eco-Flow +booster heater

Hot water thread	External thread
Hot water flow l/min	17
Drain diameter	22
Drain flow l/s	1
Drain conn. inlet	Bottom;Behind;Right
Floor drain needed	Yes
Remarks (drain)	Drain hose 2 m included
Sound level dB	61
Heat load sensitive W	1200
Heat load latent W	500
Boiler power kW	4.2
Power type	electric
Operation type	electronical
Cleaning	washing program
Washing basket size mm	500x500
Programmability	ready programs;programmable
Amount of programs	3
Insulation	insulated
Method of washing	normal wash
Drain pump	Yes
Model	WD-4S