

## Chilled display Metos Green OE-112-72-E-R290

Metos Green OE-112-72-E is a recessed, self-serve chilled display designed for use under demanding conditions, with a width of 1125 mm and height of 720 mm. The simple squared shape of the chilled display highlights the products being sold.

The display's tempered glass side panels, the glass shelf and the bright LED lighting for shelves and the cold tub make products being sold highly visible. The self-service display is open on the customer side, with hinged glass doors on the seller's side. A 215 mm high cooled tub with Gastronorm dimensioning.

In addition, the display is equipped with an auto-defrost function, the melting water from which is directed to the grey water system. For those installation locations where it is not possible to connect the display to the grey water system, an condensate evaporation tank is included as an accessory.

The display is equipped with air cooled chilling, digital temperature control and a fan speed regulator. Air temperature range is +2...+4 °C. The glass side panels and glass shelf is made from tempered glass. The substructure is made from stainless steel and insulation is polyurethane.

- recessable into furniture (cut out size 1065 x 670 m)
- shelf and tub lighting
- tempered glass side panels and shelf
- sales space 0.8 m<sup>2</sup>
- temperature area +2...+4 °C
- digital temperature regulation
- ventilator speed regulator
- easy to clean

EXTRA ACCESSORIES (can be ordered separately):

- sneeze guard for shelf
- price tag frame;
- evaporation



tank; Manual or Electrical 1000W tank; Manual or Electrical 1000W

## Chilled display Metos Green OE-112-72-E-R290

Product capacity	3x GN1/1
Item width mm	1125
Item depth mm	695
Item height mm	720/1395
Package volume	1.975
Unit of volume	m3
Package volume	1.975 m3
Package length	125
Package width	100
Package height	158
Package unit of dimension	cm
Package dimensions (LxWxH)	125x100x158 cm
Net weight	180
Net weight	180 kg
Gross weight	210
Package weight	210 kg
Unit of weight	kg
Connection power kW	0.724
Fuse Size A	10
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50
Drain diameter	30
Cooling capacity W	1020
Type of the refrigerant	R290
Sound level dB	70
Energy class rating	G