

Trolley washer Metos WD-18CW with 2 doors and floor mounting WD-TOUCH

Energy efficient trolley washer for numerous different trolleys and items. Washing compartment are 1070 x 1030x 1850 mm

- several trolleys can be normally washed together, depending on their size

- high capacity 30 - 40 washing cycles / hour
- with washing trolley (optional accessory) can be washed up to 240 plastic food transportation boxes / hour
- minimal energy and water consumption
- only 6 liters of water per cycle without heat
- unique washing process with rotating trolleys dried using centrifugation
- automatic doors
- one person can easily operate the machine
- 14 days HACCP in standard delivery
- WEB Tool diagnostics
- trolley model and picture needs to informed when ordering the machine
- control system: touch panel
- the machine is delivered in two pcs. a) 260 x 220 x 240cm b) 240 x 220 x 110cm

optional accessory:

- customized washing compartment max. size 1350 x 1350 x 1850mm (height)
- washing trolley for food transportation boxes
- 90 days HACCP registry
- cost and consumption registry



Trolley washer Metos WD-18CW with 2 doors and floor mounting WD-TOUCH

Product capacity	max. 250 kg
Item width mm	2467
Item depth mm	1836
Item height mm	2637
Package volume	21.12
Unit of volume	m3
Package volume	21.12 m3
Package length	400
Package width	220
Package height	240
Package unit of dimension	cm
Package dimensions (LxWxH)	400x220x240 cm
Net weight	1350
Net weight	1350 kg
Gross weight	1450
Package weight	1450 kg
Unit of weight	kg
Connection power kW	52.5
Fuse Size A	80
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Type of electrical connection	Fixed
Electrical conn. height mm	2700
Cold water diam.	3/4"
Cold water flow l/min	30
Cold water min pressure kPa	300
Cold water conn. height mm	2700
Hot water diam.	3/4"

Trolley washer Metos WD-18CW with 2 doors and floor mounting WD-TOUCH

Hot water flow l/min	30
Hot water min pressure kPa	300
Hot water conn. height mm	2700
Drain diameter	50
Drain flow l/s	3
Drain conn. height mm	0
Pneumatic diameter	R1/2"
Pneumatic pressure kPa	600
Heat load sensitive W	6500
Heat load latent W	4500
Boiler power kW	12
Pneumatic consumption l/min	50
Power type	electric
Operation type	electronical
Cleaning	washing program
Programmability	ready programs;programmable
Drain pump	No
Automatic hood lift	Yes
Model	WD-18CW