

Soppkittel innfällbar Metos D-I 9 l

Infällbar modell. Används som vattenvämeri

- separat värmestyrning med termostat
- konstruktion i rostfritt stål
- rostfri innerdel 9 l, locket med gångjärn
- lock 1/3 rostritt stål, 2/3 glas
- rostfri innerdel med två handtag



Soppkittel innfällbar Metos D-I 9 I

Bredd mm	263/312
Djup mm	263/312
Höjd mm	260
Paketvolym	0,03
Volymenhet	m3
Paketvolym	0,03 m3
Längd på förpackning	33
Bredd på förpackning	33
Höjd på förpackning	28
Förpackningsstorlek	cm
Dimensioner på förpackning (LxBxH)	33x33x28 cm
Nettovikt	8,5
Nettovikt med ental	8,5 kg
Bruttovikt	9
Vikt inkl. emballage	9 kg
Viktenhet	kg
Anslutningseffekt kW	0,35
Spänning V	230
Antal faser	1NPE
Frekvens Hz	50
Typ av anslutning	Stickkontakt
Avlopp, diameter	1/2"
Remarks (misc.)	öppning Ø274 mm



**Drop-in serving kettle
Metos D-19 I**

Dimensions:

- A = flange
- C = diameter
- E = cut out
- F = width innerpan over the handles
- G = build in height
- H = height above counter with innerpan and lid
- J = build in height with drainkit (drainkit to be ordered separately)
- y x z = cut out operating panel

heating element 230V, 350W
weight (empty): 7 kg

When constructing the counter, an opening for the connection cable must be considered.

The opening must be at least the size of a plug (diameter min. 40 mm). In addition, the edges of the opening must be finished to make sure that the connection cable is not damaged by rubbing against the opening edge.

The counter, where drop-in units are installed, must be damp-proof and strong enough to bear the appliance weight.

