

## Tumble dryer Metos SD10 vented

Galvanized steel 198 litres cylinder. Solid door

- oversized lint filter located in front for easy cleaning
- powerful exhaust blower assures short drying times and low operating costs
- wide door opening of 180° for easy loading and unloading
- 4 drying programs
- LED indication of the status of the program
- time remaining countdown
- top, front and side panels in anthracite gray
- must connect to exhaust chimney



## Tumble dryer Metos SD10 vented

|                            |                 |
|----------------------------|-----------------|
| Product capacity           | 10 kg           |
| Item width mm              | 683             |
| Item depth mm              | 711             |
| Item height mm             | 1027            |
| Package volume             | 0.721           |
| Unit of volume             | m3              |
| Package volume             | 0.721 m3        |
| Package length             | 74              |
| Package width              | 84              |
| Package height             | 116             |
| Package unit of dimension  | cm              |
| Package dimensions (LxWxH) | 74x84x116 cm    |
| Net weight                 | 68              |
| Net weight                 | 68 kg           |
| Gross weight               | 73              |
| Package weight             | 73 kg           |
| Unit of weight             | kg              |
| Connection power kW        | 5.3             |
| Fuse Size A                | 16              |
| Connection voltage V       | 400             |
| Number of phases           | 3NPE            |
| Frequency Hz               | 50              |
| Protection rating (IP)     | X4              |
| Operation type             | electronical    |
| Drum material              | stainless steel |
| Programmability            | ready programs  |
| Amount of programs         | 4               |
| Insulation                 | insulated       |