

Bulk brewer Metos ComBi-line 10W NG wallmounted model

Metos CB 10W NG is an easy-to-use, fast and reliable wall-mounted brewing unit equipped with a hot water tap brewing unit from which filtering takes place on a cart into a ten litres reservoir. By combining the filtering unit with an electrically heated or insulated container and a cart that meets your needs, you get the right coffee point for your use.

The amount of coffee filtration is selectable in litres or cups on the clear touch screen of the cooker. The display of the device controls the user when using the cooker and the dispensing of the ground coffee. The cooker has a timer with which coffee filtering or the hot water system can be timed to start at a certain time. The cooker capacity is around 60 litres per hour (around 480 cups). The filter does not start if the tank is not in position and the filter arm is turned over the tank. The flow of the filtering process can be monitored on the screen. The display can also check the total or daily consumption of coffee and coffee powder. After the coffee has been completed, the cooker informs you on the display and with the tone. The water temperature of the hot water hose in the body is adjustable from 60°C to 97°C, factory setting at 90°C. The capacity is 60 litres of hot water per hour, single-serving 4.1 litres. The volume of the insulated boiler is 5.6 litres. The energy saving function lowers the hot water temperature to 60°C if no hot water has been used during the last two hours.

The Metos CB 10W NG coffee urn works on a flow-through heating principle, so the appliance uses only cold and



oxygen-rich water in the filtration and keeps the water temperature right throughout the filtration. According to the water hardness set, the descaling need detector indicates the need for descaling of the boiler. The body is made of stainless steel, front of aluminum.

- a hot water tap
- filter capacity approx. 60 l / h (approx. 480 coffee cups), hot water 60l/h
- the filtering amount can be selected in litres or cups
- filtering tone
- descaling need indicator
- filter arm limit sensor
- tank detector
- the hot water temperature can be adjusted from 60 °C...97°C
- touch screen
- wall model

ACCESSORIES (to be ordered separately):

- 10 l electrically heated coffee container with sealing lid
- filter funnel for 10 l tank
- mixing tube for 10 l tank
- tea strainer for 10 l tank
- filler neck for 10 l tank
- glass hose brush
- coffee, tea and hot water stickers
- filter paper 152/457 (500 unit packs) oxygen-rich water in the filtration and keeps the water temperature right throughout the filtration. According to the water hardness set, the descaling need detector indicates the need for descaling of the boiler. The body is made of stainless steel, front of aluminum.

- a hot water tap
- filter capacity approx. 60 l / h (approx. 480 coffee cups), hot water 60l/h
- the filtering amount can be selected in litres or cups
- filtering tone
- descaling need indicator
- filter arm limit sensor
- tank detector
- the hot water temperature can be adjusted from 60 °C...97°C
- touch screen
- wall model

ACCESSORIES (to be ordered separately):

- 10 l electrically heated coffee container with sealing lid
- filter funnel for 10 l tank
- mixing tube for 10 l tank
- tea strainer for 10 l tank
- filler neck for 10 l tank
- glass hose brush
- coffee, tea and hot water stickers
- filter paper 152/457 (500 unit packs)

Bulk brewer Metos ComBi-line 10W NG wallmounted model

Product capacity	60 litres/hour
Item width mm	235
Item depth mm	489
Item height mm	799
Package volume	0.106
Unit of volume	m3
Package volume	0.106 m3
Package length	25.5
Package width	50.9
Package height	81.9
Package unit of dimension	cm
Package dimensions (LxWxH)	25.5x50.9x81.9 cm
Net weight	15
Net weight	15 kg
Gross weight	16
Package weight	16 kg
Unit of weight	kg
Connection power kW	8.4
Fuse Size A	16
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Type of electrical connection	Semifixed
Electrical conn. height mm	25
Cold water diam.	19
Cold water flow l/min	3
Cold water min pressure kPa	400
Cold water conn. height mm	25
Floor drain needed	Yes

Bulk brewer Metos ComBi-line 10W NG wallmounted model

Programmability

programmable