

Refrigerated Display Metos Halo 1R800 LED

Cold LED display with round shaped design and effective refrigeration made of plexi glass. LED light under front of each shelf

- cold display is intended for the short-term storage and distribution of pre-refrigerated foodstuffs and beverages
- light-weighted doors with handles
- refrigerated basin 104 mm (basin 534x657, fits 2 x GN1/1-65 without additional basin supports)
- airflow cools efficiently basin and 2 glass shelves
- tested in climate class 3 (temperature +25 °C and humidity 60 %)
- easily sliding doors in back of display, GN-pans can be easily fitted from the back
- basin easy to remove and clean
- glass shelves made of hardened glass
- automatic evaporation system
- adjustable feet +15 /- 45mm
- stainless steel frame structure

Accessories/features, to be ordered separately:

- handle-free doors
- laminated panelling
- flat or tube-shaped tray slides
- kick plates
- air flow grid
- adaptation for central cooling and drainage
- covering plate in front to achieve even colder display temperatures



Refrigerated Display Metos Halo 1R800 LED

Item width mm	800
Item depth mm	650
Item height mm	1500
Package volume	1.44
Unit of volume	m3
Package volume	1.44 m3
Package length	100
Package width	80
Package height	180
Package unit of dimension	cm
Package dimensions (LxWxH)	100x80x180 cm
Net weight	143.09
Net weight	143.09 kg
Gross weight	168.09
Package weight	168.09 kg
Unit of weight	kg
Connection power kW	0.9
Fuse Size A	10
Connection voltage V	220-240
Number of phases	1NPE
Frequency Hz	50
Startup current A	6.5
Protection rating (IP)	43
Type of electrical connection	Plug
Type of the refrigerant	R290
Quantity of refrigerant g	130