

Convection oven Metos REC023, 4x2/3 GN

The electric convection oven Metos REC023 with capacity of 4x2/3 GN is equipped with the classic electromechanical controls: simple and comfortable to use, with precise adjustments and great reliability in its results.

- convection air +70°C ... +300°C
- convection with humidifier
- timed or continuous operating modes
- electromechanical with manual control
- selector cooking time programmable up to 120 minutes, with warning buzzer at end of cooking time
- humidifier with automatic regulation
- cavity vent and lights
- side runners
- distance between layers 70mm
- stainless steel cooking compartment with long radius rounded corners for a perfect cleaning
- cooking compartment 25 mm thermic insulation
- double glazed door with large air interspace and inner heat reflecting type of glass for a perfect heat insulation and better efficiency
- oven front panel seal made with heat and age resistant silicon rubber
- opening fan protection cover for a proper cleaning of fan wheel
- cooking compartment heating elements of armoured AISI 321 type
- safety thermostat
- cooking compartment safety device for pressure built-up and depression
- fan motor thermic protection
- mechanical door switch

OPTIONAL - TO BE REQUESTED WHEN ORDERING OVEN

- extra charge for energy saving system connection



Convection oven Metos REC023, 4x2/3 GN

Product capacity	4xGN2/3-65
Item width mm	640
Item depth mm	565
Item height mm	525
Package volume	0.342
Unit of volume	m3
Package volume	0.342 m3
Package length	72
Package width	66
Package height	72
Package unit of dimension	cm
Package dimensions (LxWxH)	72x66x72 cm
Net weight	34
Net weight	34 kg
Gross weight	42
Package weight	42 kg
Unit of weight	kg
Connection power kW	2.6
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50
Protection rating (IP)	X3
Cold water diam.	3/4"
Drain diameter	30
Operation type	electromechanical
Hinge location	right
Cleaning	hand wash
GN size	2/3

Convection oven Metos REC023, 4x2/3 GN

Temperature area °C	50-250
Temperature probe	No
Fill in trolleys	No
Hand shower	No
Descaling	No
Humidification	Yes
Timer	Yes