

Granule dishwasher Metos WD-100 GR Touch F 400V3N~

Front loaded model. The WD-Touch display guides you through the washing process with an intuitive touch screen. Easy navigation with built-in user manuals.

- great capacity in a little space: 8 pcs. of GN1/1-65 cleaned with one programme
- patented washing system guarantees a good washing and drying result thanks to the high speed centrifuging
- hygiene warranty eases up the HACCP: the electronics of the machine controls the washing process
- amazingly low running costs: the machine uses only a. 6 litres fresh water in the final rinse. This also leads to lower consumption of energy, rinse aid and detergent.
- effective condensing and heat recovery
- six washing programmes: three with granules (the granule washing time is adjustable) and three without. The washing programmes include centrifuging.
- two granule pumps provide a high pressure for efficient performance.
- tank volume 145 l

Standard equipment:

- 1 x cassette
- 3 x lid holder
- 4 x pot grid
- 3 x small holder for 1/2 GN container
- 1 x long holder for 1/2 GN container
- 1 x cleaning scraper
- 10 kg of granule



Granule dishwasher Metos WD-100 GR Touch F 400V3N~

Product capacity	88pcs x GN 1/1-containers / h
Item width mm	1051
Item depth mm	1187
Item height mm	1969/2155
Package volume	3.704
Unit of volume	m3
Package volume	3.704 m3
Package length	122
Package width	132
Package height	230
Package unit of dimension	cm
Package dimensions (LxWxH)	122x132x230 cm
Net weight	485
Net weight	485 kg
Gross weight	555
Package weight	555 kg
Unit of weight	kg
Connection power kW	21
Fuse Size A	35
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	55
Type of electrical connection	Fixed
Electrical conn. height mm	1969
Cold water diam.	3/4"
Cold water flow l/min	18
Cold water min pressure kPa	200
Cold water conn. height mm	1969

Granule dishwasher Metos WD-100 GR Touch F 400V3N~

Hot water diam.	3/4"
Hot water thread	Internal thread
Hot water flow l/min	18
Hot water conn. height mm	1969
Drain diameter	50
Drain flow l/s	3
Drain conn. inlet	Bottom;Behind
Drain conn. height mm	178
Floor drain needed	Yes
Sound level dB	70
Ventilation machine m ³ /h	900
Boiler power kW	9
Power type	electric
Operation type	electronical
Cleaning	washing program
Features	8x1/1GN
Programmability	ready programs
Amount of programs	6
Insulation	insulated
Drain pump	No
Model	WD-100 GR