

Glass door cooler Metos Maxiglass LG3/150LG, left- handed

The Metos Maxiglass LG3/150LG glass door cooler is mainly designed to display bottled drinks and beverage containers in an aesthetically pleasing manner as well as the preservation of various drinks at a suitable temperature. Enhanced technology and unit components make the cooler more energy efficient and therefore more environmentally friendly without having to make any compromises in the appearance of the unit or its cooling capacity.

The cooler holds 151 pcs 0.30 l bottles. Effective and energy-efficient fans ensure the uniform and quick circulation of cold air in the entire cooler. Refrigerant R600a used is environmentally friendly. The cooler has a top-mounted digital thermostat and temperature can be adjusted between +2°C...+18°C (factory setting +6°C). Finishing colour is anthracite and this model is with left-handed glass door with lock.

The height of the Metos Maxiglass Noverta glass door cooler LG3/150LG is 840 mm, which allows for the device to be installed beneath a workspace. The glass door cooler has two solid flat shelves. Dimmable white LED lighting provides bright and uniform lighting and temptingly accentuates the drinks.

- low model (height 840...850 mm)
- left-handed glass door
- capacity 151/0.30 l bottles, 150 liters
- the temperature can be regulated between +2°C...+18°C
- two solid shelves
- door lock
- LED-lighting 440 Lumen
- anthracite finish
- replaceable door seals
- automated defrost and defrost water evaporation
- digital thermostat
- refrigerant R600a



Glass door cooler Metos Maxiglass LG3/150LG, left-handed

Product capacity	98x33 cl /151x30 cl btl
Item width mm	600
Item depth mm	576
Item height mm	840/850
Package volume	0.409
Unit of volume	m3
Package volume	0.409 m3
Package length	61.4
Package width	95
Package height	70.2
Package unit of dimension	cm
Package dimensions (LxWxH)	61.4x95x70.2 cm
Net weight	55
Net weight	55 kg
Gross weight	61
Package weight	61 kg
Unit of weight	kg
Connection power kW	0.95
Fuse Size A	6
Connection voltage V	220-240
Number of phases	1NPE
Frequency Hz	50/60
Type of electrical connection	Plug
Cooling capacity W	156
Type of the refrigerant	R600a
Sound level dB	55
Annual power cons. kWh	330