

# Upper shelf Metos Proff2 US-1200-1H

Construction and upper shelf of stainless steel. Width of s/s upper shelf 280 mm

- one-sided sneeze guard of tempered glass
- halotherm heating lamps



## Upper shelf Metos Proff2 US-1200-1H

Item width mm	1200
Item depth mm	507
Item height mm	405
Package volume	0.336
Unit of volume	m3
Package volume	0.336 m3
Package length	122
Package width	52
Package height	53
Package unit of dimension	cm
Package dimensions (LxWxH)	122x52x53 cm
Net weight	15
Net weight	15 kg
Gross weight	15
Package weight	15 kg
Unit of weight	kg
Connection power kW	0.6
Fuse Size A	16
Connection voltage V	230
Number of phases	1N
Type of electrical connection	Semifixed

## Upper shelf Metos Proff2 US-1200-1H

Product capacity	1200x650mm plane+13 GN1/1-100
Item width mm	1200
Item depth mm	650
Item height mm	900
Package volume	1.031
Unit of volume	m3
Package volume	1.031 m3
Package length	125

## Upper shelf Metos Proff2 US-1200-1H

Package width	75
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	125x75x110 cm
Net weight	95
Net weight	95 kg
Gross weight	95
Package weight	95 kg
Unit of weight	kg
Connection power kW	0.6
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50/60
Startup current A	2.7
Protection rating (IP)	43
Type of electrical connection	Plug
Operation type	electromechanical
Cleaning	hand wash
GN size	13 GN1/1-100
Number of chambers	3
Power range kW	0.6
Lighting	without lighting
Fill in trolleys	No
Humidification	No
Timer	No

## Upper shelf Metos Proff2 US-1200-1H

Product capacity	1200x650mm plane+13 GN1/1-100
Item width mm	1200
Item depth mm	650

## Upper shelf Metos Proff2 US-1200-1H

Item height mm	900
Package volume	1.073
Unit of volume	m3
Package volume	1.073 m3
Package length	130
Package width	75
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	130x75x110 cm
Net weight	95
Net weight	95 kg
Gross weight	95
Package weight	95 kg
Unit of weight	kg
Connection power kW	1.4
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50/60
Startup current A	6.3
Protection rating (IP)	43
Type of electrical connection	Plug
Operation type	electromechanical
Cleaning	hand wash
GN size	13 GN1/1-100
Number of chambers	3
Power range kW	1.4
Lighting	without lighting
Fill in trolleys	No

## Upper shelf Metos Proff2 US-1200-1H

Humidification	No
Timer	No

## Upper shelf Metos Proff2 US-1200-1H

Product capacity	1200x650mm plane+13 GN1/1-100
Item width mm	1200
Item depth mm	650
Item height mm	900
Package volume	1.031
Unit of volume	m3
Package volume	1.031 m3
Package length	125
Package width	75
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	125x75x110 cm
Net weight	95
Net weight	95 kg
Gross weight	95
Package weight	95 kg
Unit of weight	kg
Connection power kW	1.4
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50/60
Startup current A	6.1
Protection rating (IP)	43
Type of electrical connection	Plug
Cleaning	hand wash
GN size	13 GN1/1-100

## Upper shelf Metos Proff2 US-1200-1H

Number of chambers	3
Power range kW	1.4

Lighting	without lighting
Fill in trolleys	No
Humidification	No
Timer	No

## Upper shelf Metos Proff2 US-1200-1H

Item width mm	1200
Item depth mm	650
Item height mm	900
Package volume	1.031
Unit of volume	m3
Package volume	1.031 m3
Package length	125
Package width	75
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	125x75x110 cm
Net weight	95
Net weight	95 kg
Gross weight	119
Package weight	119 kg
Unit of weight	kg
Connection power kW	1.4
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50
Startup current A	6.3
Protection rating (IP)	43

## Upper shelf Metos Proff2 US-1200-1H

Type of electrical connection	Plug
Operation type	electromechanical
Cleaning	hand wash
GN size	8

Power range kW	1.4
Lighting	without lighting
Amount of drawers	8
Fill in trolleys	No
Humidification	No
Timer	No

## Upper shelf Metos Proff2 US-1200-1H

Item width mm	1200
Item depth mm	650
Item height mm	900
Package volume	1.031
Unit of volume	m3
Package volume	1.031 m3
Package length	125
Package width	75
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	125x75x110 cm
Net weight	95
Net weight	95 kg
Gross weight	95
Package weight	95 kg
Unit of weight	kg
Connection power kW	0.6
Fuse Size A	16
Connection voltage V	230

## Upper shelf Metos Proff2 US-1200-1H

Number of phases	1NPE
Frequency Hz	50/60
Startup current A	2.7
Protection rating (IP)	43
Type of electrical connection	Plug

Cleaning	hand wash
Number of chambers	8
Power range kW	0.6
Lighting	without lighting
Fill in trolleys	No
Humidification	No
Timer	No

## Upper shelf Metos Proff2 US-1200-1H

Product capacity	3xGN1/1-210 + 9XGN1/1-100
Item width mm	1200
Item depth mm	650
Item height mm	900
Package volume	0.963
Unit of volume	m3
Package volume	0.963 m3
Package length	125
Package width	70
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	125x70x110 cm
Net weight	85
Net weight	85 kg
Gross weight	93
Package weight	93 kg
Unit of weight	kg

## Upper shelf Metos Proff2 US-1200-1H

Connection power kW	2.2
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50/60
Startup current A	9.5
Protection rating (IP)	43



Type of electrical connection	Plug
Operation type	electromechanical
Cleaning	hand wash
GN size	3xGN1/1-210 + 9XGN1/1-100
Number of chambers	3
Power range kW	2.2
Lighting	without lighting
Fill in trolleys	No
Humidification	No
Timer	No

## Upper shelf Metos Proff2 US-1200-1H

Product capacity	3xGN1/1-210 + 9XGN1/1-100
Item width mm	1200
Item depth mm	650
Item height mm	900
Package volume	0.963
Unit of volume	m3
Package volume	0.963 m3
Package length	125
Package width	70
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	125x70x110 cm

## Upper shelf Metos Proff2 US-1200-1H

Net weight	95
Net weight	95 kg
Gross weight	105
Package weight	105 kg
Unit of weight	kg
Connection power kW	2.2
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE

Frequency Hz	50/60
Startup current A	9.8
Protection rating (IP)	43
Type of electrical connection	Plug
Function	warm
GN size	3xGN1/1-210 + 9XGN1/1-100
Power range kW	2.2
Lighting	without lighting
Type of display	with doors
Upper part	without upper part
Model	Proff
Amount of cabinets	3
Stowage	shelves

## Upper shelf Metos Proff2 US-1200-1H

Product capacity	3 X GN1/1-150 bain marie
Item width mm	1200
Item depth mm	650
Item height mm	900
Package volume	0.702
Unit of volume	m3
Package volume	0.702 m3

## Upper shelf Metos Proff2 US-1200-1H

Package length	120
Package width	65
Package height	90
Package unit of dimension	cm
Package dimensions (LxWxH)	120x65x90 cm
Net weight	85
Net weight	85 kg
Gross weight	85
Package weight	85 kg
Unit of weight	kg

Connection power kW	1.65
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50/60
Startup current A	7.2
Protection rating (IP)	43
Type of electrical connection	Plug
Operation type	electromechanical
Cleaning	hand wash
GN size	3 X GN1/1-150
Power range kW	1.65
Lighting	without lighting
Fill in trolleys	No
Humidification	No
Timer	No