

Bean to cup machine Metos OptiBean 3 Touch

One bean canister, about 1,5 kg/200 cups. One 1,6 l milk powder canister, about 970 gr/138 cups

- one 1,6 l chocolate powder container, about 1000 gr/ 60 cups
- espresso brewer unit: 6,5-9,5 grams/50-150 ml, grinder with ceramic burrs (Ditting®)
- make one or two cups at once
- the coffee beans are ground while you wait
- hourly capacity 120 cups (á 120 ml)
- brewing time for 120 ml about 25-30 seconds
- intuitive touchscreen interface
- separate taps for coffee and hot water
- OptiLight (LED) illumination, which can be adjusted
- stainless steel boiler and frame, black plastic panels
- boiler volume 1,1 ltr, heating time 3 min and temperature range 70-95° C
- adjustable cup tray 60-115 mm, max. height 167 mm
- signal when the waste canister(about 130 cups) or drip tray is full
- automatic cleaning program
- Energy saving function
- four adjustable feet
- prepared for telemetry (EVA DTS / MDB / DEX-UCS)



Bean to cup machine Metos OptiBean 3 Touch

Product capacity	250 cups/day
Item width mm	409
Item depth mm	565
Item height mm	792
Package volume	0.23
Unit of volume	m3
Package volume	0.23 m3
Package length	45
Package width	60
Package height	85
Package unit of dimension	cm
Package dimensions (LxWxH)	45x60x85 cm
Net weight	39
Net weight	39 kg
Gross weight	45
Package weight	45 kg
Unit of weight	kg
Connection power kW	2.275
Fuse Size A	16
Connection voltage V	220-240
Number of phases	1N
Frequency Hz	50/60
Protection rating (IP)	X3
Type of electrical connection	Semifixed
Electrical conn. height mm	25
Cold water diam.	3/4"
Cold water min pressure kPa	400
Cold water conn. height mm	25
Sound level dB	65

Bean to cup machine Metos OptiBean 3 Touch

Energy index	A+
Cleaning	washing program
Temperature area °C	+90°C
Features	90 cups/hour
Programmability	programmable
Tap height mm	167
Portion size	120 ml