

Freezer room MSRF 2418

230V 1N~

Cold area -18...-22°C. Supplied in elements

- 80mm polyurethane insulation
- automatic temperature control and electronic thermostat with number display
- automatic defrost and evaporation of condensation water
- supplied with 4 shelf tiers, made of plastic accepted in food industry , adjustable every 50 mm.
- interior and exterior finish of steel plate with white polyester coating
- lockable door and interior light
- Optional extras: room without floor elements, extra shelves available in s/s, floor heat resistance



Freezer room MSRF 2418 230V 1N~

| | |
|-------------------------------|----------------|
| Product capacity | 6860 l |
| Item width mm | 2400 |
| Item depth mm | 1800 |
| Item height mm | 2100 |
| Package volume | 3.62 |
| Unit of volume | m3 |
| Package volume | 3.62 m3 |
| Package length | 102 |
| Package width | 155 |
| Package height | 229 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 102x155x229 cm |
| Net weight | 430 |
| Net weight | 430 kg |
| Gross weight | 440 |
| Package weight | 440 kg |
| Unit of weight | kg |
| Connection power kW | 1.33 |
| Fuse Size A | 16 |
| Connection voltage V | 230 |
| Number of phases | 1N |
| Frequency Hz | 50 |
| Type of electrical connection | Plug |
| Electrical conn. height mm | 2100 |
| Type of the refrigerant | R290 |
| Quantity of refrigerant g | 149 |