

Griddle chromium Metos Diamante D92/10FTEC with open cupboard

Electric griddle Metos D92/10SFTEC with chromium plate - smooth, is equipped with all the power, robustness and functionality you need to work efficiently.

- Open cupboard version, smooth chromium plate
- Stainless steel coating with Scotch Brite finish
- 15 mm thick cooking plate totally independent of the top
- Large canal canopy along the entire perimeter of the plate for the collection of cooking residues, inclined towards the front for the decolouration of the liquids in the large drawer
- Large fat collection drawer
- Uniform cooking temperature on the whole plate. Optimizing the heat in the cooking area and increasing the comfort of operators in the kitchen.
- Plate not welded to the machine with optimization of the structural points subjected to thermal stress
- Too full cap in stainlessness, equipped as standard for the management of the flooding of the canals
- Plate not welded to speed up maintenance interventions and any replacements in users
- reduced energy power, an increase in yield per cm² which allows a reduction in consumption up to 15% compared to traditional versions
- Heating by means of armored resistances in incoloy
- Thermostatically controlled cooking temperature and adjustable from 110 to 280 ° C
- Safety thermostat



Griddle chromium Metos Diamante D92/10FTEC with open cupboard

| | |
|----------------------------|-------------|
| Item width mm | 400 |
| Item depth mm | 900 |
| Item height mm | 870 |
| Package volume | 0.415 |
| Unit of volume | m3 |
| Package volume | 0.415 m3 |
| Package length | 45 |
| Package width | 95 |
| Package height | 97 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 45x95x97 cm |
| Net weight | 95 |
| Net weight | 95 kg |
| Gross weight | 105 |
| Package weight | 105 kg |
| Unit of weight | kg |
| Connection power kW | 7.5 |
| Connection voltage V | 400 |
| Number of phases | 3NPE |
| Frequency Hz | 50/60 |
| Protection rating (IP) | X4 |