

## Washer extractor Metos FX80

Freestanding washer with stainless steel top panel and anthracite grey front and side panel. Large door opening Ø 410 mm for easy loading and unloading

- stainless steel Ø 530 mm drum
- wash speed 49 rpm
- extraction: 1165 rpm
- X control - easy to use microprocessor with 15 pre-set programs
- spin 400 G-factor
- easy access to all vital parts from the front
- patented soap hopper
- large drain valve (Ø76 mm)
- frequency controlled motor
- PowerWash® perforated lifting ribs more mechanical action, lower water consumption
- measurement of unbalance by means of frequency inverter
- SuperEco washing programmes
- significantly reduces water and electricity consumption

Accessories:

- plinth 135 mm
- plinth 200 mm



## Washer extractor Metos FX80

Product capacity	8 kg
Item width mm	710
Item depth mm	790
Item height mm	1115
Package volume	0.784
Unit of volume	m3
Package volume	0.784 m3
Package length	75
Package width	84
Package height	124.5
Package unit of dimension	cm
Package dimensions (LxWxH)	75x84x124.5 cm
Net weight	185
Net weight	185 kg
Gross weight	200
Package weight	200 kg
Unit of weight	kg
Connection power kW	6
Fuse Size A	16
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	44
Type of electrical connection	Semifixed
Electrical conn. inlet	Top;Behind
Electrical conn. height mm	1010
Remarks (electrical)	Heating power 6kW
Cold water diam.	3/4"
Cold water flow l/min	20

## Washer extractor Metos FX80

Cold water min pressure kPa	100
Cold water max pressure kPa	800
Cold water conn. inlet	Top;Behind
Cold water conn. height mm	1010
Hot water diam.	3/4"
Hot water flow l/min	20
Hot water conn. inlet	Top;Behind
Hot water conn. height mm	920
Drain conn. inlet	Behind;Right
Drain conn. height mm	88
Floor drain needed	Yes
Sound level dB	65
Type	electric
Operation type	electronical
Hinge location	right
Drum material	stainless steel
Programmability	ready programs
Amount of programs	15
Insulation	insulated
Drain pump	No