

Washer extractor Metos FX105

Freestanding washer with stainless steel top panel and anthracite grey front and side panel. Large door opening Ø 410 mm for easy loading and unloading

- stainless steel Ø 620 mm drum, volume 105 litres
- wash speed 49 rpm
- extraction: 1075 rpm
- X control - easy to use microprocessor with 15 pre-set programs
- spin 400 G-factor
- easy access to all vital parts from the front
- patented soap hopper
- large drain valve (Ø76 mm)
- frequency controlled motor
- PowerWash® perforated lifting ribs more mechanical action, lower water consumption
- measurement of unbalance by means of frequency inverter
- SuperEco washing programmes
- significantly reduces water and electricity consumption

Accessories:

- plinth 135 mm
- plinth 200 mm



Washer extractor Metos FX105

| | |
|-------------------------------|--------------------|
| Product capacity | 11 kg |
| Item width mm | 795 |
| Item depth mm | 795 |
| Item height mm | 1225 |
| Package volume | 1.106 |
| Unit of volume | m3 |
| Package volume | 1.106 m3 |
| Package length | 83.5 |
| Package width | 98.5 |
| Package height | 134.5 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 83.5x98.5x134.5 cm |
| Net weight | 255 |
| Net weight | 255 kg |
| Gross weight | 275 |
| Package weight | 275 kg |
| Unit of weight | kg |
| Connection power kW | 9 |
| Fuse Size A | 20 |
| Connection voltage V | 400 |
| Number of phases | 3NPE |
| Frequency Hz | 50 |
| Protection rating (IP) | 44 |
| Type of electrical connection | Semifixed |
| Electrical conn. inlet | Top;Behind |
| Electrical conn. height mm | 1120 |
| Remarks (electrical) | Heating power 9kW |
| Cold water diam. | 3/4" |
| Cold water flow l/min | 20 |

Washer extractor Metos FX105

| | |
|-----------------------------|----------------------------|
| Cold water min pressure kPa | 100 |
| Cold water max pressure kPa | 800 |
| Cold water conn. inlet | Top;Behind |
| Cold water conn. height mm | 1030 |
| Remarks (cold water) | water consumption 7,2 l/kg |
| Hot water diam. | 3/4" |
| Hot water flow l/min | 20 |
| Hot water conn. inlet | Top;Behind |
| Drain conn. inlet | Behind;Right |
| Drain conn. height mm | 88 |
| Floor drain needed | Yes |
| Sound level dB | 65 |
| Type | electric |
| Operation type | electronical |
| Hinge location | right |
| Drum material | stainless steel |
| Programmability | ready programs |
| Amount of programs | 15 |
| Insulation | insulated |
| Drain pump | No |